

AD CUBE



TECHNICAL SPECIFICATIONS:

ADBLUE TANK DISPENSER MOD. AD CUBE: Square, double wall, high-density PE. The external tank is reinforced by twin steel bands and has storage capacity equal to 100% of the inner tank.

The BASIC version is fitted with:

- Electropump, flow rate 30 L/min-220V;
- Delivery hose, 6 m.;
- Automatic delivery nozzle;
- Interstitial space leak detection system;
- Floating level indicator;
- 2" loading port with TO-DO dry break connection;
- Closing/protection lid.

The PREMIUM version is fitted with:

- Electropump, flow rate 30 L/min-220V;
- Digital flow meter mod. K24;
- Delivery hose, 8 m, with automatic hose reel;
- Electrical heating device;
- Automatic delivery nozzle;
- Interstitial space leak detection system;
- Floating level indicator;
- 2" loading port with TO-DO dry break connection;
- Closing/protection lid.



MODEL	CAPACITY (L.)	DIMENSIONS (MM)	WEIGHT (KG)	FLOW RATE
AD CUBE 15	1.500	1.200 x 1.150 x h. 1.800	190 / 205	30 lt./min. - 220 V.
AD CUBE 25	2.500	1.200 x 1.800 x h. 1.800	250 / 265	30 lt./min. - 220 V.
AD CUBE 50	5.000	2.400 x 2.300 x h. 1.800	200 / 215	30 lt./min. - 220 V.