

TT EASY Eex

TECHNICAL DETAILS :

Mobile **GASOLINE** refueling unit for fuel transport and for direct machineries refueling operations on site through pump unit included. Permitted for transportation for direct consumption according to **ADR 1.1.3.1 c)**. Easy to carry and to handle, These special PE transportable tanks are equipped with forklift pockets.

TTs Easy Eex are available on following versions: 120 l and 190 l capacity. Made in electrically conductive highly crosslinked polyethylene, tanks are complete with:

- Patented flame suppressant filling;
- Integrated nozzle holder;
- Integrated breathing valve;
- Integrated forklift pockets;
- Integrated handles;
- Pump unit with self priming, **electric pump** 12V DC Eex (40 lpm) , with automatic nozzle on 2.7 m filling hose or **manual pump** or manual pump (25 lpm) with normal nozzle installed on 2.7 m length delivery hose;
- Electric cable with clamps for battery connection;
- Grounding cable for safe refueling operations;

Optional cover lid.



**FLAME SUPPRESSANT
FILLING ANTISTATICA**



TTE 190 - 12 Eex



TTE 120 - M Eex

MODEL	CAPACITY (L.)	DIMENSIONS (MM)	WEIGHT (KG)	FLOW RATE	PUMP
TTE 120 - M Eex	120	800 x 600 x 470	26	25 lt./min.	Manual
TTE 190 - M Eex	190	800 x 600 x 610	38	25 lt./min.	Manual
TTE 120 - 12 Eex	120	800 x 600 x 470	36	40 lt./min.	12 V. DC
TTE 190 - 12 Eex	190	800 x 600 x 610	38	40 lt./min.	12 V. DC