

DT CUBE

TECHNICAL SPECIFICATIONS :

Square, double wall, low-density PE, vertical tank. The external tank is reinforced by twin steel bands and has storage capacity equal to 100% of the inner tank.

The DT CUBE is available in the different capacities (1000, 1500 and 2500 L).

Available in the BASIC and PREMIUM versions.



The **DT CUBE BASIC** is fitted with :

- Electropump mod. Panther 56, flow rate 50 L/min-220V
- Digital flow meter mod. K24
- Delivery hose, 5 m, with 1" couplings
- Automatic delivery nozzle
- Interstitial space leak detection system
- Floating level indicator
- 2" loading port
- Overfill prevention valve at 90%
- Pump start-stop device, with pump stop on minimum level by means of pressure switch
- Closing/protection lid



The **DT CUBE PREMIUM** is fitted with :

- Electropump mod. Panther 56, flow rate 50 L/min-220V
- Mechanical flow meter for private use mod. K33
- Delivery hose, 8 m, with automatic hose reel
- Automatic delivery nozzle
- Interstitial space leak detection system
- Water absorption kit
- Floating level indicator
- 2" loading port
- Overfill prevention valve at 90%
- Pump start-stop device, with pump stop on minimum level by means of pressure switch
- Closing/protection lid

MODEL	CAPACITY (L.)	DIMENSIONS (MM)	WEIGHT (KG)	FLOW RATE
DT CUBE 10	1.000	1.200 x 800 x h. 1.800	125 / 150	50 lt./min. - 220 V.
DT CUBE 15	1.500	1.200 x 1.150 x h. 1.800	165 / 180	50 lt./min. - 220 V.
DT CUBE 25	2.500	1.200 x 1.800 x h. 1.800	215 / 235	50 lt./min. - 220 V.

