

TT SQUARE ADR



TECHNICAL DATA

FULLY BUNDED AND SEALED TANK made in carbon steel with internal baffles, **approved by the Italian Ministry of Infrastructures and Transport**, built in accordance with **ADR regulations and UN marked**. The tank is suitable for the transport of flammable liquid fuel class II and III and is stackable when full.

Available in two capacities: 960 liters - horizontal version (TT SQUARE ADR 960) and 440 liters - vertical (TT SQUARE ADR 440).

The tank is fitted into a palletized metallic container which acts as a containment basin, with a capacity higher than 110% of the tank capacity.

TT SQUARE ADR is equipped with:

- Lockable lid.
- Corner lifting lugs.
- Forklift pockets for easy handling.
- Generator connection port (also with closed and locked lid).
- Outer tank total drainage point with cap.

FEATURES:

- Inspection hatch, diameter 200 mm, with gasket and bolted cover.
- Loading port in brass/aluminium with 3" quick connection point.
- Homologated triple-effect safety valve.
- Mechanical level indicator.
- 12V electric pump (or 24V on request), flow rate 65 L/min for the 9K version or 50 L/min for the 12K version. Equipped with 5 m delivery hose and automatic nozzle.

OPTIONAL ELEMENTS

Digital **FUEL METER** model K24.

WATER ABSORPTION FILTER kit.

QUICK CONNECTION COUPLING kit, size 1/2", for connection to generator (suction, return and feeding lines).

HOSE REEL with 1" x 6 m hose (for TT SQUARE ADR 960).



Code	Model	Capacity (lt.)	Dimensions (mm.)	Weight (kg)	Pump flow rate
411001-2	TT SQUARE ADR 440 - 9K	440	980 x 980 x 1220h	221	65 l/min
411001-1	TT SQUARE ADR 440 - 12K	440	980 x 980 x 1220h	221	50 l/min
411002-2	TT SQUARE ADR 960 - 9K	960	1130 x 1530 x 1330h	404	65 l/min
411002-1	TT SQUARE ADR 960 - 12K	960	1130 x 1530 x 1330h	404	50 l/min