

## TT CADDY DIESEL



**TT CADDY DIESEL 55**



**TT CADDY DIESEL 110**

### TECHNICAL DATA

**TRANSPORTABLE, TROLLEY-TYPE TANK** made in polyethylene, in exemption from ADR according paragraph 1.1.3.1.C for the transport of fuel, ideal for refuelling small vehicles and machinery, and ideal to transport and dispense Diesel fuel. The TT CADDY DIESEL has ergonomic grip for safe handling and lifting and puncture proof wheels designed for use on any type of ground. In addition to lightness and handiness, the structure, devoid of sharp edges, and the reinforcement ribs confer great strength and resistance to the unit. The TT CADDY DIESEL can be filled either horizontally or vertically with the same amount of fuel.

The TT CADDY tanks is equipped with:

- Top handle for easy gripping and lifting
- Integrated grooves for tank securing with ratchet straps
- Suction/drain safety ball valve
- Filling plug with integrated non-spill vent
- Lower handle for easier lifting
- Puncture proof wheels and base support.
- Frontal nozzle holder
- Manual and electric pump housing

#### DC BATTERY PUMP:

DC battery pump, 12 V, 40 l/min, with 4 m electric cable, clamps for battery connection and automatic nozzle.

#### MANUAL PUMP:

Manual rotary vane pump made in aluminum with manual nozzle and 3 m hose.

#### OPTIONAL ELEMENTS:

Digital **FLOW METER** model K24.

Stainless steel impurity separator **FILTER** 60μ.



Code	Model	Capacity (lt.)	Dimensions (mm.)	Weight (kg)	Pump
ADR0601	TT CADDY 55 12V	55	460 x 360 x 900h	8	Electric 12V
ADR0601M	TT CADDY MANUAL	55	460 x 360 x 900h	8	Manual
ADR0101	TT CADDY 110 12V	110	460 x 440 x 1100h	12	Electric 12V
ADR0100	TT CADDY MANUAL	110	460 x 440 x 1100h	12	Manual