

ECO OIL

TECHNICAL DATA

CONTAINER FOR STORAGE OF WASTE OILS compliant with the Italian Legislative Decree n. 95 of 27 January 1992, with the Italian Ministerial Decree n. 392 dated 16 May 1996 and with the European Directives 75/439/CEE and 87/10/CEE, regarding exhaust and waste oils disposal.

Made of roto-moulded high-density polyethylene, these tanks have high mechanical properties, high impact strength, and also thermal, chemical, UV rays and adverse weather conditions resistance.

ECO OIL is designed and manufactured to exceed all the latest requirements relating to the safe storage and disposal of waste oils. Ideal solution for garages, depots, workshops, civic amenity sites, landfill sites, harbours and many other fields of applications.

ECO OIL consists of a double wall tank and is equipped with a lockable top hinged lid with inside a mesh for filter drainage.


ECO OIL is available in black version for mineral oil or in green version for vegetal oil.

ECO OIL is complete with:

- Top screwed hatch for drainage, diameter Ø 125 mm.
- Hydrostatic tank content gauge.
- Lockable top hinged lid with mesh for filter drainage.
- Visual leak detector system to check the interstitial space between the two containers.

OPTIONAL ELEMENTS

SAFETY LOCK for screwed lid.



Code	Model	Capacity (lt.)	Colour	Dimensions (mm.)
31003	OE 300	300	black	Ø 820 x 1080h
31005	OE 500	500	black	Ø 960 x 1240h
32003	OV 300	300	green	Ø 820 x 1080h
32005	OV 500	500	green	Ø 960 x 1240h