

# TT CADDY EEX



TT CADDY EEX 55



TT CADDY EEX 110

## **TECHNICAL DATA**

**TRANSPORTABLE, TROLLEY-TYPE TANK** made in polyethylene, **in accordance with ADR regulations** for the transport of fuel, ideal for refuelling small vehicles and machinery, and ideal to transport and dispence Diesel fuel. The TT CADDY DIESEL has ergonomic grip for safe handling and lifting and puncture proof wheels designed for use on any type of ground. In addition to lightness and handiness, the structure, devoid of sharp edges, and the reinforcement ribs confer great strength and resistance to the unit. The TT CADDY DIESEL can be filled either horizontally or vertically with the same amount of fuel.

The TT CADDY tanks is equipped with:

- Top handle for easy gripping and lifting
- Integrated grooves for tank securing with ratchet straps
- Suction/drain safety ball valve
- Filling plug with integrated non-spill vent
- Lower handle for easier lifting
- Puncture proof wheels and base support.
- Frontal nozzle holder
- Manual and electric pump housing

### DC BATTERY PUMP:

DC battery pump, Ex-50 ATEX 12 V, 40 l/min, with 4 m electric cable, clamps for battery connection and automatic nozzle with 3 m antistatic hose.

#### MANUAL PUMP:

Manual rotary vane pump made in aluminum with manual nozzle and 3 m hose.

### **OPTIONAL ELEMENTS:**

Digital **FLOW METER** model K24 ATEX for gasoline. Water absorbing **FILTER**. Impurities absorbing **FILTER**, 60 µ. Water (60 µ) and impurities (5 µ) separator **FILTER**.



The company reserves the right to modify the information contained in this catalogue withoout any prior notice.







Code	Model	Capacity (It.)	Dimensions (mm.)	Weight (kg)	Pump
ADR055EX50	TT CADDY EEX 55 EX 50	55	460 x 360 x 900h	8	Electric 12V
ADR055M	TT CADDY EEX 55 M	55	460 x 360 x 900h	8	Manual
ADR0110EX50	TT CADDY EEX 110 EX 50	110	460 x 440 x 1100h	12	Electric 12V
ADR0110M	TT CADDY EEX 110 M	110	460 x 440 x 1100h	12	Manual