advanced fluid systems

TT MOBILE EEX



TT MOBILE EEX 220



TECHNICAL DATA

The **TT MOBILE EEX** is a linear polyethylene tank designed for Gasoline fuel transport **in accordance with ADR regulation**. It is fitted with: lockable lid (optional for mod. 220), built-in forklift pockets, handles for lifting and carrying the empty tank and integrated grooves for securing the tank with ratchet straps during transport. All fittings are made in materials compatible with Gasoline.

The TT MOBILE EEX is equipped with:

- DC fuel transfer pump, mod. ATEX Ex-50 12 or 220 V, 50 I/min for Gasoline.
- 4 m antistatic hose.
- ATEX automatic nozzle.
- 4 m battery power cable and clamps for battery connection.
- Aluminum filling plug, size 2", equipped with emergency vent valve (air vent valve).
- Level indicator for.
- In-Line filter.

OPTIONAL ELEMENTS:

Digital **FLOW METER** model K24 ATEX for gasoline.

Water absorbing **FILTER**.

Impurities absorbing **FILTER**, 60 μ.

Water (60 μ) and impurities (5 μ) separator **FILTER**.

POLYETHYLENE LID for mod. 220.





Code	Model	Capacity (It.)	Dimensions (mm.)	Weight (kg)	Pump
3422000	TT MOBILE EEX 220 12V	220	910 x 600 x 665h	24	12V
3422001	TT MOBILE EEX 220 220V	220	910 x 600 x 665h	24	220V
3433000	TT MOBILE EEX 330 12V	330	1200 x 800 x 650h	32	12V
3433001	TT MOBILE EEX 330 220V	330	1200 x 800 x 650h	32	220V

TT MOBILE EEX tank are not available for italian market

The company reserves the right to modify the information contained in this catalogue withoout any prior notice