

## TT MOBILE PICK-UP

### TECHNICAL DATA



The **TT MOBILE PICK-UP** is specifically designed for easy installation of the tank into the back of pick-up vehicles, thanks to its narrow base allowing for positioning between the vehicle wheel arches. The tank is made in linear polyethylene and is suitable for the storage, transfer and transport of Diesel fuel **in exemption from ADR according paragraph 1.1.3.1.C** (as well as AdBlue®/DEF transport for the COMBI version).

The TT MOBILE PICK-UP is equipped with:

- DC fuel transfer pump, mod. DEVIL40 12V 40 l/min for Diesel fuel.
- Submersible pump 12V 15 l/min for AdBlue®/DEF (COMBI version).
- 4 m hose for Diesel fuel.
- 4 m hose for AdBlue®/DEF (COMBI version).
- Automatic nozzle for Diesel fuel.
- Manual nozzle for AdBlue®/DEF (COMBI version).
- 4 m battery power cable and clamps for battery connection.
- Aluminum filling plug, size 2", equipped with emergency vent valve (air vent valve).
- Polyethylene filling plug, size 2" (COMBI version).
- Level indicator for Diesel fuel.
- In-Line filter for Diesel fuel.

### OPTIONAL ELEMENTS

Digital **METER** model K24 (for Diesel).  
**WATER ABSORBING FILTER**, 30 µm.



## TT MOBILE DIESEL PICK-UP



Diesel fuel  
 AdBlue®/DEF



## TT MOBILE COMBI PICK-UP

Code	Model	Capacity (lt.)	Total dimensions (mm.)	Base dimensions (mm.)	Weight (kg)	Pumps
3733001-1	TT MOBILE DIESEL 330 PICK-UP	330	1200 x 800 x 700h	1010 x 770	44	Electric 12V
3744001-1	TT MOBILE DIESEL 440 PICK-UP	440	1200 x 800 x 830h	1010 x 770	52	Electric 12V
3944010-1	TT MOBILE COMBI PICK-UP	400+50 (diesel+AdBlue®)	1200 x 800 x 830h	1010 x 770	57	Electric 12V